

Printing date 05/29/2018

Reviewed on 04/06/2015

## 1 Identification

- **Product identifier**
- **Trade name:** P12 Pine
- **Article number:** 1012188
- **Application of the substance / the mixture** Polyester filler
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**  
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:  
 31200 Stephenson Hwy  
 Madison Heights, MI 48071  
 USA

Manufacturing Site:  
 1611 Hults Drive  
 Eaton Rapids, MI 48827  
 USA  
 ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**  
 During normal opening times: +1 (248) 588-2270  
 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US

Printing date 05/29/2018

Reviewed on 04/06/2015

Trade name: P12 Pine

(Contd. of page 1)

 · **Hazard pictograms**


GHS02 GHS07 GHS08

 · **Signal word** Warning

 · **Hazard-determining components of labeling:**

Styrene

N,N-dimethylaniline

 · **Hazard statements**

Flammable liquid and vapor.

Harmful if swallowed.

Causes skin and eye irritation.

Suspected of causing cancer.

 · **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

 · **Classification system:**

 · **NFPA ratings (scale 0 - 4)**


Health = 1

Fire = 3

Reactivity = 0

 · **HMIS-ratings (scale 0 - 4)**


HEALTH 1 Health = 1

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

 · **Other hazards**

 · **Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

US

(Contd. on page 3)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/06/2015

Trade name: P12 Pine

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 100-42-5 EINECS: 202-851-5	Styrene	20-50%
CAS: 121-69-7 EINECS: 204-493-5	N,N-dimethylaniline	≥0.25-<1%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**  
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.  
· **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.

(Contd. on page 4)

Printing date 05/29/2018

Reviewed on 04/06/2015

**Trade name: P12 Pine**

(Contd. of page 3)

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

100-42-5	Styrene	20 ppm
65997-17-3	Fibrous Glass	15 mg/m <sup>3</sup>
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
546-93-0	Magnesite	45 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
121-69-7	N,N-dimethylaniline	10 ppm
64-17-5	ethanol	1,800 ppm
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
21645-51-2	aluminium hydroxide	8.7 mg/m <sup>3</sup>

- **PAC-2:**

100-42-5	Styrene	130 ppm
65997-17-3	Fibrous Glass	170 mg/m <sup>3</sup>
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m <sup>3</sup>
546-93-0	Magnesite	260 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
121-69-7	N,N-dimethylaniline	330 ppm
64-17-5	ethanol	3300* ppm
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
21645-51-2	aluminium hydroxide	73 mg/m <sup>3</sup>

- **PAC-3:**

100-42-5	Styrene	1100* ppm
65997-17-3	Fibrous Glass	990 mg/m <sup>3</sup>
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m <sup>3</sup>
546-93-0	Magnesite	1,600 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
121-69-7	N,N-dimethylaniline	2,000 ppm
64-17-5	ethanol	15000* ppm
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
21645-51-2	aluminium hydroxide	440 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**

- **Precautions for safe handling** No special precautions are necessary if used correctly.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

(Contd. on page 5)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/06/2015

Trade name: P12 Pine

(Contd. of page 4)

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

#### 100-42-5 Styrene

ACGIH TLV	Short-term value: 170 at 40 ppm mg/m <sup>3</sup> Long-term value: 85 at 20 ppm mg/m <sup>3</sup>
OSHA PEL	Long-term value: 100 ppm mg/m <sup>3</sup> Ceiling limit value: 200 ppm mg/m <sup>3</sup>
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m <sup>3</sup> , 100 ppm Long-term value: 215 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: (170) mg/m <sup>3</sup> , (40) ppm Long-term value: (85) NIC-8.5 mg/m <sup>3</sup> , (20) NIC-2 ppm BEI, NIC-A3, NIC-OTO

#### 121-69-7 N,N-dimethylaniline

PEL	Long-term value: 25 mg/m <sup>3</sup> , 5 ppm Skin
REL	Short-term value: 50 mg/m <sup>3</sup> , 10 ppm Long-term value: 25 mg/m <sup>3</sup> , 5 ppm Skin
TLV	Short-term value: 50 mg/m <sup>3</sup> , 10 ppm Long-term value: 25 mg/m <sup>3</sup> , 5 ppm Skin; BEI-M

· **Ingredients with biological limit values:**

#### 121-69-7 N,N-dimethylaniline

BEI	1.5 % of hemoglobin Medium: blood Time: during or end of shift Parameter: Methemoglobin (background, nonspecific, semi-quantitative)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 6)

US

**Trade name: P12 Pine**

(Contd. of page 5)

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Thixotropic Paste
<b>Color:</b>	Pine
<b>Odor:</b>	Pungent
<b>Odor threshold:</b>	Not determined.
- **pH-value:** Not determined.
- **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	145 °C (293 °F)
- **Flash point:** 31 °C (87.8 °F)
- **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 7)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/06/2015

Trade name: P12 Pine

(Contd. of page 6)

· <b>Ignition temperature:</b>	490 °C (914 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	0.9 Vol %
<b>Upper:</b>	6.8 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	6 hPa (4.5 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.95 g/cm <sup>3</sup> (7.93 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	0.2 %
<b>VOC content:</b>	20.42 %
	194.0 g/l / 1.62 lb/gl
· <b>Solids content:</b>	40.1 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
- ?
- Carbon monoxide and carbon dioxide

US

(Contd. on page 8)

Printing date 05/29/2018

Reviewed on 04/06/2015

Trade name: P12 Pine

(Contd. of page 7)

## 11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

### 100-42-5 Styrene

Oral	LD50	316 mg/kg (rat)
Inhalative	LC50/4 h	24 mg/l (rat)

- Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
 

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful  
Irritant
- Carcinogenic categories

· IARC (International Agency for Research on Cancer)

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
100-42-5	Styrene	2B
112926-00-8	Precipitated silica (Silica-Amorphous)	3
13463-67-7	titanium dioxide	2B
121-69-7	N,N-dimethylaniline	3
64-17-5	ethanol	1
7631-86-9	silicon dioxide, chemically prepared	3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
  - Bioaccumulative potential: No further relevant information available.
  - Mobility in soil: No further relevant information available.
- Additional ecological information:
  - General notes:
 

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
  - Results of PBT and vPvB assessment
    - PBT: Not applicable.
    - vPvB: Not applicable.

(Contd. on page 9)



Printing date 05/29/2018

Reviewed on 04/06/2015

Trade name: P12 Pine


· **Other adverse effects** No further relevant information available.

(Contd. of page 8)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· <b>UN-Number</b> · <b>DOT, IMDG, IATA</b>	UN1866
· <b>UN proper shipping name</b> · <b>DOT</b> · <b>IMDG, IATA</b>	Resin solution RESIN SOLUTION
· <b>Transport hazard class(es)</b> · <b>DOT</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Packing group</b> · <b>DOT</b>	III
· <b>Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b> · <b>EMS Number:</b>	Not applicable. F-E, S-E
· <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	not regulated

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

(Contd. on page 10)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/06/2015

Trade name: P12 Pine

(Contd. of page 9)

· **Section 313 (Specific toxic chemical listings):**

100-42-5 Styrene

121-69-7 N,N-dimethylaniline

· **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2) rule:**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-42-5 Styrene

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 ethanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6 Talc (Mg<sub>3</sub>H<sub>2</sub>(SiO<sub>3</sub>)<sub>4</sub>)

A4

13463-67-7 titanium dioxide

A4

121-69-7 N,N-dimethylaniline

A4

64-17-5 ethanol

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

· **Listed in CWC Regulations**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Styrene

(Contd. on page 11)

US



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/06/2015

**Trade name: P12 Pine**

(Contd. of page 10)

*N,N*-dimethylaniline

· **Hazard statements**

Flammable liquid and vapor.

Harmful if swallowed.

Causes skin and eye irritation.

Suspected of causing cancer.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Date of preparation / last revision** 05/29/2018 / 2

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Car. 2: Carcinogenicity – Category 2