



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 04/07/2015

1 Identification

- **Product identifier**
- **Trade name:** P78 White
- **Article number:** 1078088
- **Application of the substance / the mixture** Polyester filler
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

US

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

*Vinyl toluene**Stoddard solvent*

· Hazard statements

*Flammable liquid and vapor.**Harmful if inhaled.**Causes skin and eye irritation.**May be fatal if swallowed and enters airways.*

· Precautionary statements

*Avoid breathing dust/fume/gas/mist/vapors/spray**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Use explosion-proof electrical/ventilating/lighting/equipment.**If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

· Classification system:

· NFPA ratings (scale 0 - 4)

*Health = 1**Fire = 2**Reactivity = 0*

· HMIS-ratings (scale 0 - 4)

*Health = 1**Fire = 2**Reactivity = 0*

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

US

(Contd. on page 3)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 25013-15-4	Vinyl toluene	10-20%
EINECS: 246-562-2		

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

US



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 3)

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

13463-67-7	titanium dioxide	30 mg/m ³
546-93-0	Magnesite	45 mg/m ³
21645-51-2	aluminium hydroxide	8.7 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
130-15-4	1,4-naphthoquinone	0.57 mg/m ³
98-29-3	4-tert-butylcatechol	0.18 mg/m ³
8052-41-3	Stoddard solvent	300 mg/m ³

· **PAC-2:**

13463-67-7	titanium dioxide	330 mg/m ³
546-93-0	Magnesite	260 mg/m ³
21645-51-2	aluminium hydroxide	73 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
130-15-4	1,4-naphthoquinone	6.3 mg/m ³
98-29-3	4-tert-butylcatechol	2 mg/m ³
8052-41-3	Stoddard solvent	1,800 mg/m ³

· **PAC-3:**

13463-67-7	titanium dioxide	2,000 mg/m ³
546-93-0	Magnesite	1,600 mg/m ³
21645-51-2	aluminium hydroxide	440 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
130-15-4	1,4-naphthoquinone	38 mg/m ³
98-29-3	4-tert-butylcatechol	560 mg/m ³
8052-41-3	Stoddard solvent	29500** mg/m ³

7 Handling and storage

· **Handling:**

· **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)

US

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

25013-15-4 Vinyl toluene

PEL	Long-term value: 480 mg/m ³ , 100 ppm
REL	Long-term value: 480 mg/m ³ , 100 ppm
TLV	Short-term value: 483 mg/m ³ , 100 ppm
	Long-term value: 242 mg/m ³ , 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Thixotropic Paste
-------	-------------------

Color:	White
--------	-------

· Odor:	Pungent
---------	---------

· Odor threshold:	Not determined.
-------------------	-----------------

· pH-value:	Not determined.
-------------	-----------------

· Change in condition

Melting point/Melting range:	Undetermined.
------------------------------	---------------

Boiling point/Boiling range:	170 °C (338 °F)
------------------------------	-----------------

· Flash point:	53 °C (127.4 °F)
----------------	------------------

· Flammability (solid, gaseous):	Not applicable.
----------------------------------	-----------------

· Decomposition temperature:	Not determined.
------------------------------	-----------------

· Auto igniting:	Product is not selfigniting.
------------------	------------------------------

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
------------------------	--

· Explosion limits:

Lower:	Not determined.
--------	-----------------

Upper:	Not determined.
--------	-----------------

· Vapor pressure:	Not determined.
-------------------	-----------------

· Density at 20 °C (68 °F):	0.92 g/cm ³ (7.68 lbs/gal)
-----------------------------	---------------------------------------

· Relative density	Not determined.
--------------------	-----------------

· Vapor density	Not determined.
-----------------	-----------------

· Evaporation rate	Not determined.
--------------------	-----------------

· Solubility in / Miscibility with

Water:	Not miscible or difficult to mix.
--------	-----------------------------------

· Partition coefficient (n-octanol/water):	Not determined.
--	-----------------

· Viscosity:

Dynamic:	Not determined.
----------	-----------------

Kinematic:	Not determined.
------------	-----------------

· Solvent content:

Organic solvents:	18.0 %
-------------------	--------

(Contd. on page 7)

US



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 6)

VOC content: 17.98 %
165.4 g/l / 1.38 lb/gl

Solids content: 48.1 %
Other information No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
?
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
25013-15-4	Vinyl toluene	3
13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3

· NTP (National Toxicology Program)

130-15-4	1,4-naphthoquinone	R
----------	--------------------	---

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 8)

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White



(Contd. of page 7)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------|
| · UN-Number | UN1866 |
| · DOT, IMDG, IATA | UN1866 |
| · UN proper shipping name | Resin solution |
| · DOT | RESIN SOLUTION |
| · IMDG, IATA | RESIN SOLUTION |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Packing group | |
| · DOT, IMDG, IATA | III |

(Contd. on page 9)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 8)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act) (Substances not listed):**

50815-87-7 Amorphous Sodium Borosilicate

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2) rule:**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

A4

25013-15-4 Vinyl toluene

A4

13463-67-7 titanium dioxide

A4

(Contd. on page 10)

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 9)

 · **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

 · **Listed in CWC Regulations**

None of the ingredients is listed.

 · **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

 · **Hazard pictograms**


GHS02 GHS07 GHS08

 · **Signal word** Danger

 · **Hazard-determining components of labeling:**

Vinyl toluene

Stoddard solvent

 · **Hazard statements**

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin and eye irritation.

May be fatal if swallowed and enters airways.

 · **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

 · **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

 · **Date of preparation / last revision** 05/31/2018 / 1

 · **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 11)



BUILDING TRUST

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 04/07/2015

Trade name: P78 White

(Contd. of page 10)

HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
Asp. Tox. 1: Aspiration hazard – Category 1

US