



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 07/15/2016

1 Identification

- **Product identifier**
- **Trade name:** APG1750 S Black
- **Article number:** 1025761
- **Application of the substance / the mixture** Polyester resin
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: APG1750 S Black

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

Vinyl toluene
methyl methacrylate
Naphtha (petroleum), hydrotreated heavy
Stoddard solvent

· Hazard statements

Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause respiratory irritation.
May be fatal if swallowed and enters airways.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2
Fire = 3
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



HEALTH 2 Health = 2
FIRE 3 Fire = 3
REACTIVITY 0 Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 3)

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: **APG1750 S Black**· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 25013-15-4 EINECS: 246-562-2	Vinyl toluene	20-50%
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate	1-5%
CAS: 136-52-7 EINECS: 205-250-6	cobalt(II) 2-ethylhexanoate	0.1-1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.

(Contd. on page 4)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: **APG1750 S Black**

(Contd. of page 3)

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

80-62-6	methyl methacrylate	17 ppm
112945-52-5	Fumed silica - untreated	18 mg/m ³
1317-61-9	triiron tetraoxide	21 mg/m ³
64-17-5	ethanol	1,800 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
150-76-5	mequinol	15 mg/m ³
123-31-9	1,4-dihydroxybenzene	3 mg/m ³
130-15-4	1,4-naphthoquinone	0.57 mg/m ³
8052-41-3	Stoddard solvent	300 mg/m ³
98-29-3	4-tert-butylcatechol	0.18 mg/m ³
108-10-1	4-methylpentan-2-one	75 ppm
142-82-5	heptane	500 ppm

· **PAC-2:**

80-62-6	methyl methacrylate	120 ppm
112945-52-5	Fumed silica - untreated	100 mg/m ³
1317-61-9	triiron tetraoxide	230 mg/m ³
64-17-5	ethanol	3300* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
150-76-5	mequinol	49 mg/m ³
123-31-9	1,4-dihydroxybenzene	20 mg/m ³
130-15-4	1,4-naphthoquinone	6.3 mg/m ³
8052-41-3	Stoddard solvent	1,800 mg/m ³
98-29-3	4-tert-butylcatechol	2 mg/m ³
108-10-1	4-methylpentan-2-one	500 ppm
142-82-5	heptane	830 ppm

· **PAC-3:**

80-62-6	methyl methacrylate	570 ppm
112945-52-5	Fumed silica - untreated	630 mg/m ³

(Contd. on page 5)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: **APG1750 S Black**

(Contd. of page 4)

1317-61-9	triiron tetraoxide	1,400 mg/m ³
64-17-5	ethanol	15000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
150-76-5	mequinol	320 mg/m ³
123-31-9	1,4-dihydroxybenzene	120 mg/m ³
130-15-4	1,4-naphthoquinone	38 mg/m ³
8052-41-3	Stoddard solvent	29500** mg/m ³
98-29-3	4-tert-butylcatechol	560 mg/m ³
108-10-1	4-methylpentan-2-one	3000* ppm
142-82-5	heptane	5000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

25013-15-4 Vinyl toluene

PEL	Long-term value: 480 mg/m ³ , 100 ppm
REL	Long-term value: 480 mg/m ³ , 100 ppm
TLV	Short-term value: 483 mg/m ³ , 100 ppm Long-term value: 242 mg/m ³ , 50 ppm

80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m ³ , 100 ppm
-----	--

(Contd. on page 6)

Trade name: APG1750 S Black

(Contd. of page 5)

REL	Long-term value: 410 mg/m ³ , 100 ppm
TLV	Short-term value: 410 mg/m ³ , 100 ppm
	Long-term value: 205 mg/m ³ , 50 ppm
	DSEN

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Black

· **Odor:** Strong, aromatic

· **Odor threshold:** Not determined.

(Contd. on page 7)

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: APG1750 S Black

(Contd. of page 6)

· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	36 °C (96.8 °F)
· Flash point:	32 °C (89.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.39 g/cm ³ (11.6 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	27.4 %
VOC content:	31.46 %
	437.2 g/l / 3.65 lb/gl
Solids content:	33.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
- ?

(Contd. on page 8)

US

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: APG1750 S Black

Carbon monoxide and carbon dioxide

(Contd. of page 7)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	4,000 mg/kg (rat)
Inhalative	LC50/4 h	7,093 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

25013-15-4	Vinyl toluene	3
80-62-6	methyl methacrylate	3
136-52-7	cobalt(II) 2-ethylhexanoate	2B
64-17-5	ethanol	1
7631-86-9	silicon dioxide, chemically prepared	3
14808-60-7	Quartz (SiO ₂)	1
123-31-9	1,4-dihydroxybenzene	3
108-10-1	4-methylpentan-2-one	2B

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
130-15-4	1,4-naphthoquinone	R

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.

(Contd. on page 9)

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: APG1750 S Black


(Contd. of page 8)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1866 |
| · UN proper shipping name | As stated below: |
| · DOT | Resin solution |
| · IMDG, IATA | RESIN SOLUTION |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Packing group | |
| · DOT | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · EMS Number: | F-E, <u>S-E</u> |
| · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

US

(Contd. on page 10)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: APG1750 S Black

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

123-31-9	1,4-dihydroxybenzene
----------	----------------------

- **Section 313 (Specific toxic chemical listings):**

80-62-6	methyl methacrylate
---------	---------------------

136-52-7	cobalt(II) 2-ethylhexanoate
----------	-----------------------------

- **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

- **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

- **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

1317-65-3	Calcium Carbonate
-----------	-------------------

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

108-10-1	4-methylpentan-2-one
----------	----------------------

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
---------	---------

108-10-1	4-methylpentan-2-one
----------	----------------------

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

80-62-6	methyl methacrylate	E, NL
---------	---------------------	-------

108-10-1	4-methylpentan-2-one	I
----------	----------------------	---

142-82-5	heptane	D
----------	---------	---

- **TLV (Threshold Limit Value established by ACGIH)**

25013-15-4	Vinyl toluene	A4
------------	---------------	----

80-62-6	methyl methacrylate	A4
---------	---------------------	----

64-17-5	ethanol	A3
---------	---------	----

14808-60-7	Quartz (SiO ₂)	A2
------------	----------------------------	----

123-31-9	1,4-dihydroxybenzene	A3
----------	----------------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

(Contd. on page 11)

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: APG1750 S Black

(Contd. of page 10)

Listed in CWC Regulations

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms


GHS02 GHS07 GHS08

Signal word *Danger*
Hazard-determining components of labeling:

Vinyl toluene
 methyl methacrylate
 Naphtha (petroleum), hydrotreated heavy
 Stoddard solvent

Hazard statements

Flammable liquid and vapor.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 Suspected of causing cancer.
 May cause respiratory irritation.
 May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 If swallowed: Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Date of preparation / last revision 05/29/2018 / 7

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)



BUILDING TRUST

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 07/15/2016

Trade name: APG1750 S Black

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

US