

Printing date 06/14/2018

Reviewed on 06/14/2018

**1 Identification**

- **Product identifier**
- **Trade name:** SC180 NA Part B Hardener
- **Article number:** 1026074
- **Application of the substance / the mixture** Epoxy curing agent
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**  
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:  
31200 Stephenson Hwy  
Madison Heights, MI 48071  
USA

Manufacturing Site:  
1611 Hults Drive  
Eaton Rapids, MI 48827  
USA  
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (248) 588-2270  
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

**2 Hazard(s) identification**

- **Classification of the substance or mixture**



GHS08 Health hazard

Repr. 1A H360 May damage fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 06/14/2018

Reviewed on 06/14/2018

Trade name: SCI180 NA Part B Hardener

(Contd. of page 1)

## · Hazard pictograms



GHS05 GHS07 GHS08

· Signal word *Danger*

## · Hazard-determining components of labeling:

Polypropylene glycol

Cycloaliphatic amine, Proprietary

Fatty acids, C18-unsat., dimers, reaction products with polyethylenepolyamines

tetraethylenepentamine

Tertiary Amine

3,6-diazaoctanethylenediamin

## · Hazard statements

*Harmful if swallowed.**Causes severe skin burns and eye damage.**May cause an allergic skin reaction.**May damage fertility or the unborn child.**May cause damage to organs through prolonged or repeated exposure.*

## · Precautionary statements

*Avoid breathing dust/fume/gas/mist/vapors/spray**Do not breathe dusts or mists.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Call a poison center/doctor if you feel unwell.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Immediately call a poison center/doctor.**Specific treatment (see on this label).**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

## · Classification system:

## · NFPA ratings (scale 0 - 4)



Health = 3

Fire = 1

Reactivity = 0

## · HMIS-ratings (scale 0 - 4)



Health = 3

Fire = 1

Reactivity = 0

## · Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 3)

Printing date 06/14/2018

Reviewed on 06/14/2018

**Trade name: SCI180 NA Part B Hardener**
· **vPvB:** Not applicable.

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 25322-69-4	Polypropylene glycol	20-50%
CAS: 68410-23-1	Fatty acids, C18-unsat., dimers, reaction products with polyethylenepolyamines	≥5-<10%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol	≥5-<10%
	Cycloaliphatic amine, Proprietary	≥2.5-<5%
CAS: 112-57-2 EINECS: 203-986-2	tetraethylenepentamine	≥1-<2.5%
	Tertiary Amine	≥1-<5%
CAS: 112-24-3 EINECS: 203-950-6	3,6-diazaoctanethylenediamin	≥0.1-<1%
CAS: 872-50-4 EINECS: 212-828-1	N-methyl-2-pyrrolidone	0.1-1%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**  
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.  
· **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

(Contd. on page 4)

Printing date 06/14/2018

Reviewed on 06/14/2018

**Trade name: SC180 NA Part B Hardener**

(Contd. of page 3)

**· Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**6 Accidental release measures**
**· Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**· Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

**· Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals**
**· PAC-1:**

471-34-1	calcium carbonate	45 mg/m <sup>3</sup>
25322-69-4	Polypropylene glycol	30 mg/m <sup>3</sup>
68410-23-1	Fatty acids, C18-unsat., dimers, reaction products with polyethylenepolyamines	30 mg/m <sup>3</sup>
100-51-6	Benzyl alcohol	30 ppm
112-57-2	tetraethylenepentamine	15 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	3 ppm
78-78-4	isopentane	3000* ppm
872-50-4	N-methyl-2-pyrrolidone	30 ppm
1309-42-8	magnesium hydroxide	26 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>

**· PAC-2:**

471-34-1	calcium carbonate	210 mg/m <sup>3</sup>
25322-69-4	Polypropylene glycol	330 mg/m <sup>3</sup>
68410-23-1	Fatty acids, C18-unsat., dimers, reaction products with polyethylenepolyamines	330 mg/m <sup>3</sup>
100-51-6	Benzyl alcohol	52 ppm
112-57-2	tetraethylenepentamine	130 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
78-78-4	isopentane	33000*** ppm
872-50-4	N-methyl-2-pyrrolidone	32 ppm
1309-42-8	magnesium hydroxide	280 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>

**· PAC-3:**

471-34-1	calcium carbonate	1,300 mg/m <sup>3</sup>
25322-69-4	Polypropylene glycol	2,000 mg/m <sup>3</sup>
68410-23-1	Fatty acids, C18-unsat., dimers, reaction products with polyethylenepolyamines	2,000 mg/m <sup>3</sup>

(Contd. on page 5)

**Trade name: SCI80 NA Part B Hardener**

(Contd. of page 4)

100-51-6	Benzyl alcohol	740 ppm
112-57-2	tetraethylenepentamine	790 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	83 ppm
78-78-4	isopentane	200000*** ppm
872-50-4	N-methyl-2-pyrrolidone	190 ppm
1309-42-8	magnesium hydroxide	1,700 mg/m <sup>3</sup>
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
 The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
 At this time, the other constituents have no known exposure limits.

<b>100-51-6 Benzyl alcohol</b>	
WEEL	Long-term value: 10 ppm
<b>112-57-2 tetraethylenepentamine</b>	
WEEL	Long-term value: 5 mg/m <sup>3</sup> Skin; DSEN
<b>112-24-3 3,6-diazaoctanethylenediamin</b>	
WEEL	Long-term value: 6 mg/m <sup>3</sup> , 1 ppm Skin
<b>872-50-4 N-methyl-2-pyrrolidone</b>	
WEEL	Long-term value: 10 ppm Skin

(Contd. on page 6)

Printing date 06/14/2018

Reviewed on 06/14/2018

**Trade name: SCI80 NA Part B Hardener**

(Contd. of page 5)

**· Ingredients with biological limit values:**

**872-50-4 N-methyl-2-pyrrolidone**

BEI	100 mg/L
	Medium: urine
	Time: end of shift
	Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**

**· Personal protective equipment:**

**· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

**· Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

**· Information on basic physical and chemical properties**

**· General Information**

**· Appearance:**

**Form:** Pasty

(Contd. on page 7)

Printing date 06/14/2018

Reviewed on 06/14/2018

Trade name: SCI180 NA Part B Hardener

(Contd. of page 6)

· <b>Color:</b>	Beige
· <b>Odor:</b>	Amine-like
· <b>Odor threshold:</b>	Not determined.
· <b>pH-value:</b>	Not determined.
· <b>Change in condition</b>	
<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	205.4 °C (401.7 °F)
· <b>Flash point:</b>	94 °C (201.2 °F)
· <b>Flammability (solid, gaseous):</b>	Not applicable.
· <b>Ignition temperature:</b>	435 °C (815 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	Not determined.
· <b>Vapor pressure at 20 °C (68 °F):</b>	1 hPa (0.8 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.77 g/cm <sup>3</sup> (6.43 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with</b>	
<b>Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	6.7 %
<b>VOC content:</b>	6.72 %
	51.6 g/l / 0.43 lb/gl
<b>Solids content:</b>	53.7 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.

(Contd. on page 8)

US



Printing date 06/14/2018

Reviewed on 06/14/2018

**Trade name: SCI180 NA Part B Hardener**

(Contd. of page 7)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
?  
Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 25322-69-4 Polypropylene glycol

Oral	LD50	541 mg/kg (rat)
------	------	-----------------

Dermal	LD50	>10,000 mg/kg (rabbit)
--------	------	------------------------

### 112-57-2 tetraethylenepentamine

Dermal	LD50	660 mg/kg (rabbit)
--------	------	--------------------

- **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO <sub>2</sub> )	I
------------	----------------------------	---

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 9)



Printing date 06/14/2018

Reviewed on 06/14/2018

**Trade name: SC180 NA Part B Hardener**

(Contd. of page 8)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |  |                 |
|--|-----------------|
| · <b>UN-Number</b>   |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>UN proper shipping name</b>   |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>Transport hazard class(es)</b>  |                 |
| · <b>DOT, ADN, IMDG, IATA</b>  |                 |
| · <b>Class</b>   | not regulated   |
| · <b>Packing group</b>   |                 |
| · <b>DOT, IMDG, IATA</b>   | not regulated   |
| · <b>Environmental hazards:</b>  | Not applicable. |
| · <b>Special precautions for user</b>  | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>  | not regulated   |

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

872-50-4 | N-methyl-2-pyrrolidone

- **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

(Contd. on page 10)

Printing date 06/14/2018

Reviewed on 06/14/2018

**Trade name: SCI180 NA Part B Hardener**

(Contd. of page 9)

**· Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

**· Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

**· TSCA new (21st Century Act) (Substances not listed)**

Cycloaliphatic amine, Proprietary

Tertiary Amine

**· Proposition 65**
**· Chemicals known to cause cancer:**

1317-65-3 Calcium Carbonate

14808-60-7 Quartz (SiO<sub>2</sub>)
**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

872-50-4 N-methyl-2-pyrrolidone

**· Carcinogenic categories**
**· EPA (Environmental Protection Agency)**

None of the ingredients is listed.

**· TLV (Threshold Limit Value established by ACGIH)**
14808-60-7 Quartz (SiO<sub>2</sub>)

A2

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**
14808-60-7 Quartz (SiO<sub>2</sub>)
**· Listed in CWC Regulations**

None of the ingredients is listed.

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**


GHS05



GHS07



GHS08

**· Signal word** Danger

**· Hazard-determining components of labeling:**

Polypropylene glycol

Cycloaliphatic amine, Proprietary

Fatty acids, C18-unsat., dimers, reaction products with polyethylenepolyamines

tetraethylenepentamine

Tertiary Amine

3,6-diazaoctanethylenediamin

(Contd. on page 11)

US

Printing date 06/14/2018

Reviewed on 06/14/2018

**Trade name: SCI180 NA Part B Hardener**

(Contd. of page 10)

**· Hazard statements**

Harmful if swallowed.  
 Causes severe skin burns and eye damage.  
 May cause an allergic skin reaction.  
 May damage fertility or the unborn child.  
 May cause damage to organs through prolonged or repeated exposure.

**· Precautionary statements**

Do not breathe dusts or mists.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If swallowed: Call a poison center/doctor if you feel unwell.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 Immediately call a poison center/doctor.  
 Specific treatment (see on this label).  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 06/14/2018 / 3

**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Corr. 1C: Skin corrosion/irritation – Category 1C  
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
 Skin Sens. 1: Skin sensitisation – Category 1  
 Repr. 1A: Reproductive toxicity – Category 1A  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2