

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

1 Identification

- **Product identifier**
- **Trade name:** EL337 Resin
- **Article number:** I337088
- **Application of the substance / the mixture** Epoxy resin
- **Details of the supplier of the safety data sheet**
Sika Advanced Resins, US
EHS Department
- **Manufacturer/Supplier:**
Supplier's Name: Sika Advanced Resins, US
Headquarters:
30800 Stephenson Hwy
Madison Heights, MI 48071
USA

advancedresins.ehs@us.sika.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carc. 1B H350 May cause cancer.
Repr. 1B H360 May damage fertility or the unborn child.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Aquatic Acute 2 H401 Toxic to aquatic life.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 1)

· Hazard pictograms



GHS07 GHS08 GHS09

· Signal word *Danger*

· Hazard-determining components of labeling:

*1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane**N-methyl-2-pyrrolidone**Reaction Product of Bisphenol A and Epichlorohydrin*

· Hazard statements

*Causes serious eye irritation.**May cause an allergic skin reaction.**May cause cancer.**May damage fertility or the unborn child.**Toxic to aquatic life.**Toxic to aquatic life with long lasting effects.*

· Precautionary statements

*Avoid breathing dust/fume/gas/mist/vapors/spray**Avoid breathing dust/fume/gas/mist/vapors/spray**Avoid release to the environment.**Wear protective gloves/protective clothing/eye protection/face protection.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**If skin irritation or rash occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Wash contaminated clothing before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



HEALTH 2 Health = *2

FIRE 1 Fire = 1

REACTIVITY 0 Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	≥20-<25%
CAS: 17557-23-2 EINECS: 241-536-7	1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane	≥5-<10%
CAS: 2530-83-8 EINECS: 219-784-2	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	≥1-<3%
CAS: 25068-38-6 NLP: 500-033-5	Reaction Product of Bisphenol A and Epichlorohydrin	≥0.25-<1%
CAS: 872-50-4 EINECS: 212-828-1	N-methyl-2-pyrrolidone	0.1-1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	30 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	9.3 mg/m ³
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	90 mg/m ³
872-50-4	N-methyl-2-pyrrolidone	30 ppm

· PAC-2:

28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	330 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	100 mg/m ³
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	990 mg/m ³
872-50-4	N-methyl-2-pyrrolidone	32 ppm

· PAC-3:

28064-14-4	Epoxy phenol novolac resin Reaction product of Phenol-Formaldehyde Novolac with Epichlorohydrin	2,000 mg/m ³
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	230 mg/m ³
25068-38-6	Reaction Product of Bisphenol A and Epichlorohydrin	5,900 mg/m ³
872-50-4	N-methyl-2-pyrrolidone	190 ppm

US

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

872-50-4 N-methyl-2-pyrrolidone

TLV	BEI
WEEL	Long-term value: 10 ppm
	Skin

- **Ingredients with biological limit values:**

872-50-4 N-methyl-2-pyrrolidone

BEI	100 mg/L
	Medium: urine
	Time: end of shift
	Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 5)

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Thixotropic Paste

Color: Grey

· **Odor:** Amine-like

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: >200 °C (>392 °F)

· **Flash point:** 110 °C (230 °F)

· **Flammability (solid, gaseous):** Not applicable.

(Contd. on page 7)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 6)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.39 g/cm ³ (11.6 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.5 %
VOC content:	0.47 %
	6.6 g/l / 0.05 lb/gal
Solids content:	21.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 7)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

- LD/LC50 values that are relevant for classification:

Oral	LD50	4,500 mg/kg (rat)
------	------	-------------------

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
13463-67-7	titanium dioxide	2B

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity

- Aquatic toxicity:

96 hr LC50	3.6 mg/l (Fish)
------------	-----------------

- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

- Ecotoxicological effects:

- Remark: Toxic for fish

- Additional ecological information:

- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

(Contd. on page 9)

US

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin


(Contd. of page 8)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT · IMDG, IATA 	<p>not regulated UN3082</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG · IATA 	<p>not regulated ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin, Epoxy Resin), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy phenol novolac resin, Epoxy Resin)</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT · Class 	<p>not regulated</p>
<ul style="list-style-type: none"> · IMDG, IATA 	
	
<ul style="list-style-type: none"> · Class · Label 	<p>9 Miscellaneous dangerous substances and articles 9</p>
<ul style="list-style-type: none"> · Packing group · DOT · IMDG, IATA 	<p>not regulated III</p>

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 9)

· Environmental hazards:	Product contains environmentally hazardous substances: Epoxy phenol novolac resin
· Marine pollutant:	Yes
· Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
· Special precautions for user	Warning: Miscellaneous dangerous substances and articles
· Danger code (Kemler):	60
· EMS Number:	F-A,S-F
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY PHENOL NOVOLAC RESIN, EPOXY RESIN), 9, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

872-50-4 N-methyl-2-pyrrolidone

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 10)

· **Proposition 65**

· **Chemicals known to cause cancer:**

1317-65-3	Calcium Carbonate
13463-67-7	titanium dioxide
1333-86-4	Carbon black
14808-60-7	Quartz (SiO ₂)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

872-50-4	N-methyl-2-pyrrolidone
----------	------------------------

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

· **Listed in CWC Regulations**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labeling:**

1,3-bis(2,3-epoxypropoxy)-2,2-dimethylpropane

N-methyl-2-pyrrolidone

Reaction Product of Bisphenol A and Epichlorohydrin

· **Hazard statements**

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

May damage fertility or the unborn child.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 11)

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 01/09/2020 / 3

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 1B: Carcinogenicity – Category 1B

Repr. 1B: Reproductive toxicity – Category 1B

(Contd. on page 13)



Safety Data Sheet
acc. to OSHA HCS

Printing date 01/09/2020

Reviewed on 01/09/2020

Trade name: EL337 Resin

(Contd. of page 12)

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
*** Data compared to the previous version altered.**

US