



**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name : Biresin® CR131 Part A

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Product use : Composites system

**1.3 Details of the supplier of the safety data sheet**

Company name of supplier : Sika Deutschland GmbH  
Kornwestheimer Str. 103-107  
D-70439 Stuttgart  
Telephone : +49 711 8009 0  
E-mail address of person responsible for the SDS : EHS@de.sika.com

**1.4 Emergency telephone number**

Emergency CONTACT (24-Hour-Number):  
GBK GmbH Global Regulatory Compliance +49(0)6132-84463

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification (REGULATION (EC) No 1272/2008)**

Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

**2.2 Label elements**

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.



Precautionary statements	:	H411 Toxic to aquatic life with long lasting effects.  <b>Prevention:</b> P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection.  <b>Response:</b> P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P391 Collect spillage.
--------------------------	---	---

Hazardous components which must be listed on the label:

- reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)
- reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
- 1,4-bis(2,3 epoxypropoxy)butane

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Components**

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6 500-033-5 01-2119456619-26-XXXX	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 60 - < 80
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	9003-36-5 500-006-8 01-2119454392-40-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 10 - < 20

**SAFETY DATA SHEET**  
 according to Regulation (EC) No. 1907/2006  
**Biresin® CR131 Part A**



Revision Date 12.11.2019

Version 5.0

Print Date 12.11.2019

1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 01-2119494060-45-XXXX	Aquatic Chronic 3; H412 Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318	>= 5 - < 10
---------------------------------	---	---	-------------

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
 Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
 Wash off with soap and plenty of water.  
 If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 Continue rinsing eyes during transport to hospital.  
 Remove contact lenses.  
 Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
 Rinse mouth with water.  
 Do not give milk or alcoholic beverages.  
 Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

- Symptoms : Allergic reactions  
 Excessive lachrymation  
 Erythema  
 Dermatitis  
 See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects  
 sensitising effects  
  
 Causes skin irritation.  
 May cause an allergic skin reaction.  
 Causes serious eye damage.



#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8.

---



---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Storage class (TRGS 510) : 10, Combustible liquids
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : Consult most current local Product Data Sheet prior to any use.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Biresin® CR131 Part A**



Revision Date 12.11.2019

Version 5.0

Print Date 12.11.2019

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm)  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

**Environmental exposure controls**

General advice : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

---

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Appearance : viscous liquid

Colour : various

Odour : epoxy-like

Odour Threshold : No data available

pH : ca. 6,6

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : > 101 °C  
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Biresin® CR131 Part A**



Revision Date 12.11.2019

Version 5.0

Print Date 12.11.2019

Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0,1 hPa
Relative vapour density	:	No data available
Density	:	ca. 1,15 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	ca. 2.000 mPa.s (25 °C)
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s (40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

## 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available



#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

Not classified based on available information.

##### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

##### **1,4-bis(2,3 epoxypropoxy)butane:**

Acute oral toxicity : LD50 Oral (Rat): 1.163 mg/kg

##### **Skin corrosion/irritation**

Causes skin irritation.

##### **Serious eye damage/eye irritation**

Causes serious eye damage.

##### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Not classified based on available information.

##### **Reproductive toxicity**

Not classified based on available information.

##### **STOT - single exposure**

Not classified based on available information.

##### **STOT - repeated exposure**

Not classified based on available information.

##### **Aspiration toxicity**

Not classified based on available information.





---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq 700$ ):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l  
aquatic invertebrates Exposure time: 48 h

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number.  
Completely emptied packagings may be given for recycling.  
Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.  
Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany.  
For further details see [www.sika.de](http://www.sika.de)



---

## SECTION 14: Transport information

### 14.1 UN number

**ADR** : UN 3082  
**IMDG** : UN 3082  
**IATA** : UN 3082

### 14.2 UN proper shipping name

**ADR** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(epoxy resin)  
**IMDG** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(epoxy resin)  
**IATA** : Environmentally hazardous substance, liquid, n.o.s.  
(epoxy resin)

### 14.3 Transport hazard class(es)

**ADR** : 9  
**IMDG** : 9  
**IATA** : 9

### 14.4 Packing group

**ADR**  
Packing group : III  
Classification Code : M6  
Hazard Identification Number : 90  
Labels : 9  
Tunnel restriction code : (-)  
**IMDG**  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous Dangerous Goods

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 964  
Packing instruction (LQ) : Y964  
Packing group : III  
Labels : Miscellaneous Dangerous Goods



#### 14.5 Environmental hazards

**ADR**

Environmentally hazardous : yes

**IMDG**

Marine pollutant : yes

**IATA (Passenger)**

Environmentally hazardous : yes

**IATA (Cargo)**

Environmentally hazardous : yes

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- |  |   |
|--|---|
| International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors  | : Not applicable  |
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).  | : None of the components are listed (= > 0.1 %).  |
| REACH - List of substances subject to authorisation (Annex XIV)  | : Not applicable  |
| Regulation (EC) No 1005/2009 on substances that deplete the ozone layer  | : Not applicable  |
| Regulation (EC) No 850/2004 on persistent organic pollutants   | : Not applicable  |
| Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals                 | : Not applicable  |
| REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) | : Conditions of restriction for the following entries should be considered:<br>Number on list 3   |
| REACH Information:   | All substances contained in our Products are<br>- registered by our upstream suppliers, and/or<br>- registered by us, and/or<br>- excluded from the regulation, and/or<br>- exempted from the registration. |



Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Water contaminating class : WGK 2 obviously hazardous to water  
(Germany) Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 0,1 %  
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0,1 %

**Other regulations:**

Product is no subject to the Chemicals Prohibition Ordinance.

**15.2 Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

---

**SECTION 16: Other information**

**Full text of H-Statements**

H302 : Harmful if swallowed.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H411 : Toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox. : Acute toxicity  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitisation  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods

**SAFETY DATA SHEET**  
according to Regulation (EC) No. 1907/2006  
**Biresin® CR131 Part A**



Revision Date 12.11.2019

Version 5.0

Print Date 12.11.2019

- LD50 : Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
- LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
- MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
- OEL : Occupational Exposure Limit
- PBT : Persistent, bioaccumulative and toxic
- PNEC : Predicted no effect concentration
- REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
- SVHC : Substances of Very High Concern
- vPvB : Very persistent and very bioaccumulative

**Further information**

**Classification of the mixture:**

Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

**Classification procedure:**

Calculation method
Calculation method
Calculation method
Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

DE / EN