

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

· **Trade name:** EPOLAM 2080 RESIN (A)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the mixture** Epoxy resin

### 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

AXSON FRANCE

15 Rue de l'Equerre - F-95310 SAINT OUEN L'AUMONE

Tél. +33 (0)1 34 40 34 60

· **Further information obtainable from:** DPT HSE - +33 (0)1 34 40 34 60 - [safety@axson.com](mailto:safety@axson.com)

· **1.4 Emergency telephone number:** ORFILA : +33 (0)1 45 42 59 59

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

Skin Corr. 1C      H314      Causes severe skin burns and eye damage.

Eye Dam. 1      H318      Causes serious eye damage.

Skin Sens. 1      H317      May cause an allergic skin reaction.

Repr. 1B      H360F      May damage fertility.

Aquatic Chronic 2      H411      Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS05   GHS07   GHS08   GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Tetraglycidylether methylene bis aniline

Trimethylolpropantriglycidylether

· **Hazard statements**

H314      Causes severe skin burns and eye damage.

H317      May cause an allergic skin reaction.

H360F      May damage fertility.

H411      Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P260      Do not breathe dusts or mists.

P280      Wear protective gloves.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310      Immediately call a POISON CENTER/doctor.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.01.2017

Version number 9

Revision: 03.11.2016

**Trade name: EPOLAM 2080 RESIN (A)**

(Contd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH205 Contains epoxy constituents. May produce an allergic reaction.

**SECTION 3: Composition/information on ingredients**

**3.2 Chemical characterisation: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 28768-32-3	Tetraglycidylether methylene bis aniline	50-100%
EINECS: 249-204-3	Aquatic Chronic 2, H411; Skin Sens. 1, H317	
CAS: 30499-70-8	Trimethylolpropantriglycidylether	25-50%
	Repr. 1B, H360F; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Sens. 1, H317	

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NO<sub>x</sub>)

**5.3 Advice for firefighters**

**Protective equipment:**

Wear fully protective suit.

Wear self-contained respiratory protective device.

**Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

GB

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.01.2017

Version number 9

Revision: 03.11.2016

Trade name: **EPOLAM 2080 RESIN (A)**

(Contd. of page 2)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections** See Section 8 for information on personal protection equipment.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
The usual precautionary measures are to be adhered to when handling chemicals.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Protection of hands:**



Protective gloves

- **Material of gloves**  
Nitrile rubber, NBR  
Butyl rubber, BR  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.01.2017

Version number 9

Revision: 03.11.2016

Trade name: **EPOLAM 2080 RESIN (A)**

(Contd. of page 3)

· **Eye protection:**

Safety glasses

Tightly sealed goggles

· **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

<b>Form:</b>	Fluid
<b>Colour:</b>	Amber coloured
<b>Odour:</b>	Light

· **Change in condition**

<b>Melting point/Melting range:</b>	NA °C
<b>Boiling point/Boiling range:</b>	>200 °C (DIN 53171)

- **Flash point:** >110 °C (ISO 2719)
- **Ignition temperature:** >300 °C (DIN 51 794)
- **Decomposition temperature:** >200 °C (DIN 53171)
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** Product does not present an explosion hazard.
- **Density at 20 °C:** 1.14 g/cm<sup>3</sup> (ISO 1675:1985)
- **Solubility in / Miscibility with water:** Insoluble.
- **organic solvents:** Soluble in many organic solvents.
- **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
May produce violent reactions with bases and numerous organic substances including alcohols and amines.  
Exothermic polymerisation.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.01.2017

Version number 9

Revision: 03.11.2016

**Trade name: EPOLAM 2080 RESIN (A)**

(Contd. of page 4)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
May damage fertility.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

**28768-32-3 Tetraglycidylether methylene bis aniline**

LC50 (96h) 7 mg / l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Dispose of the product by burning in a suitable incinerator or bury in an approved landfill following all applicable local and/or national regulations.

#### European waste catalogue

20 01 27\* paint, inks, adhesives and resins containing dangerous substances

#### Uncleaned packaging:

#### Recommendation:

Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed.  
Disposal must be made according to official regulations.

GB

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.01.2017




Version number 9

Revision: 03.11.2016

Trade name: **EPOLAM 2080 RESIN (A)**

(Contd. of page 5)

### SECTION 14: Transport information

- \* . **14.1 UN-Number**  
 . **ADR, IMDG, IATA** UN1760  
 . **14.2 UN proper shipping name**  
 . **ADR** 1760 CORROSIVE LIQUID, N.O.S.  
 (Trimethylolpropantriglycidylether), ENVIRONMENTALLY HAZARDOUS  
 . **IMDG** CORROSIVE LIQUID, N.O.S.  
 (Trimethylolpropantriglycidylether, Epoxy resins), MARINE POLLUTANT  
 . **IATA** CORROSIVE LIQUID, N.O.S.  
 (Trimethylolpropantriglycidylether)  
 . **14.3 Transport hazard class(es)**  
 . **ADR, IMDG**
-  
- . **Class** 8 Corrosive substances.  
 . **Label** 8
- 
- . **IATA**
- 
- . **Class** 8 Corrosive substances.  
 . **Label** 8  
 . **14.4 Packing group** III  
 . **ADR, IMDG, IATA** III  
 . **14.5 Environmental hazards:** Product contains environmentally hazardous substances:  
 Epoxy resins  
 . **Marine pollutant:** Yes  
 Symbol (fish and tree)  
 . **Special marking (ADR):** Symbol (fish and tree)  
 . **14.6 Special precautions for user** Warning: Corrosive substances.  
 . **Danger code (Kemler):** 80  
 . **EMS Number:** F-A,S-B  
 . **Stowage Category** A  
 . **Stowage Code** SW2 Clear of living quarters.  
 . **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.  
 . **Transport/Additional information:**
- 
- . **ADR**  
 . **Limited quantities (LQ)** 5L  
 . **Excepted quantities (EQ)** Code: E1  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 1000 ml  
 . **Transport category** 3  
 . **Tunnel restriction code** E

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.01.2017

Version number 9

Revision: 03.11.2016

**Trade name: EPOLAM 2080 RESIN (A)**

(Contd. of page 6)

- **IMDG**
- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 1760 CORROSIVE LIQUID, N.O.S.  
(TRIMETHYLOLPROPANTRIGLYCIDYLETHER), 8, III,  
ENVIRONMENTALLY HAZARDOUS

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Relevant phrases**  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H360F May damage fertility.  
H411 Toxic to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Skin Corr. 1C: Skin corrosion/irritation – Category 1C  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1  
Repr. 1B: Reproductive toxicity – Category 1B  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- **\* Data compared to the previous version altered.**