



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/10/2018

Reviewed on 09/23/2015

1 Identification

- **Product identifier**
- **Trade name:** EL336 Hardener
- **Article number:** 1501389-1
- **Application of the substance / the mixture** Epoxy curing agent
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07

- **Signal word** Danger

(Contd. on page 2)

US



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: **EL336 Hardener**

(Contd. of page 1)

- **Hazard-determining components of labeling:**

cyclohex-1,2-ylenediamine
 3,6-diazaoctanethylenediamin
 m-phenylenebis(methylamine)
 1-methylimidazole
 1,6-Hexanediamine, 2,2,4 (or 2,4,4)-trimethyl-

- **Hazard statements**

Causes severe skin burns and eye damage.
 May cause an allergic skin reaction.
 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray
 Do not breathe dusts or mists.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Wash contaminated clothing before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.
 · **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 694-83-7	cyclohex-1,2-ylenediamine	20-50%
EINECS: 211-776-7		

(Contd. on page 3)

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: **EL336 Hardener**

(Contd. of page 2)

CAS: 112-24-3 EINECS: 203-950-6	3,6-diazaoctanethylenediamin	≥20-<25%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine)	10-20%
CAS: 616-47-7 EINECS: 210-484-7	1-methylimidazole	≥5-<10%
CAS: 931-36-2 EINECS: 213-234-5	2-ethyl-4-methylimidazole	1-5%
CAS: 25513-64-8 EINECS: 247-134-8	1,6-Hexanediamine, 2,2,4 (or 2,4,4)-trimethyl-	≥0.1-<1%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)

US

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: **EL336 Hardener**

(Contd. of page 3)

- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

694-83-7	cyclohex-1,2-ylenediamine	2.1 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	3 ppm
616-47-7	1-methylimidazole	2.3 mg/m ³
119-36-8	methyl salicylate	2.3 ppm
628-63-7	pentyl acetate	100 ppm
822-36-6	4-methylimidazole	10 mg/m ³

· **PAC-2:**

694-83-7	cyclohex-1,2-ylenediamine	23 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
616-47-7	1-methylimidazole	25 mg/m ³
119-36-8	methyl salicylate	25 ppm
628-63-7	pentyl acetate	670 ppm
822-36-6	4-methylimidazole	110 mg/m ³

· **PAC-3:**

694-83-7	cyclohex-1,2-ylenediamine	140 mg/m ³
112-24-3	3,6-diazaoctanethylenediamin	83 ppm
616-47-7	1-methylimidazole	150 mg/m ³
119-36-8	methyl salicylate	150 ppm
628-63-7	pentyl acetate	4000* ppm
822-36-6	4-methylimidazole	150 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: **EL336 Hardener**

(Contd. of page 4)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

112-24-3 3,6-diazaoctanethylenediamin	
WEEL	Long-term value: 6 mg/m ³ , 1 ppm
	Skin

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:** Not required.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Light yellow

(Contd. on page 6)

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: *EL336 Hardener*

(Contd. of page 5)

· Odor:	<i>Amine-like</i>
· Odor threshold:	<i>Not determined.</i>
· pH-value:	<i>Not determined.</i>
· Change in condition	
Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>188 °C (370.4 °F)</i>
· Flash point:	<i>105 °C (221 °F)</i>
· Flammability (solid, gaseous):	<i>Not applicable.</i>
· Ignition temperature:	<i>335 °C (635 °F)</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>Product does not present an explosion hazard.</i>
· Explosion limits:	
Lower:	<i>Not determined.</i>
Upper:	<i>Not determined.</i>
· Vapor pressure:	<i>Not determined.</i>
· Density at 20 °C (68 °F):	<i>0.99 g/cm³ (8.26 lbs/gal)</i>
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with	
Water:	<i>Not miscible or difficult to mix.</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
Organic solvents:	<i>0.0 %</i>
Water:	<i>0.1 %</i>
VOC content:	<i>0.04 %</i>
	<i>0.4 g/l / 0.00 lb/gl</i>
Solids content:	<i>2.0 %</i>
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*

(Contd. on page 7)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: **EL336 Hardener**

(Contd. of page 6)

- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
?
Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

112-24-3 3,6-diazaoctanethylenediamin

Oral	LD50	2,500 mg/kg (rat)
Dermal	LD50	805 mg/kg (rabbit)

1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	1,040 mg/kg (rat)
Inhalative	LC50/4 h	2.4 mg/l (rat)

616-47-7 1-methylimidazole

Oral	LD50	1,400 mg/kg (mouse)
------	------	---------------------

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

822-36-6	4-methylimidazole	2B
----------	-------------------	----

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

1477-55-0 m-phenylenebis(methylamine)

72 or 96 hr ErC50	12 mg/l (Chaetogammarus marinus)
-------------------	----------------------------------

(Contd. on page 8)

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: EL336 Hardener


(Contd. of page 7)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|-------------------------------------|--|
| · UN-Number | |
| · DOT, IMDG, IATA | UN3267 |
| · UN proper shipping name | |
| · DOT | Corrosive liquid, basic, organic, n.o.s. (Triethylenetetramine, m-phenylenebis(methylamine)) |
| · IMDG, IATA | CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (TRIETHYLENETETRAMINE, m-phenylenebis(methylamine)) |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 8 Corrosive substances |
| · Label | 8 |

(Contd. on page 9)

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: **EL336 Hardener**

(Contd. of page 8)

· **IMDG, IATA**

· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· Segregation Code	SG35 Stow "separated from" acids.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L

· **IMDG**

· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (TRIEETHYLENETETRAMINE, M-PHENYLENEBIS(METHYLAMINE)), 8, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

(Contd. on page 10)

US



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: EL336 Hardener

(Contd. of page 9)

· **TSCA (Toxic Substances Control Act) (Substances not listed):**

930-62-1 | 2,4-dimethyl-1H-imidazole

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

822-36-6 | 4-methylimidazole

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Listed in CWC Regulations**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

cyclohex-1,2-ylenediamine

3,6-diazaoctanethylenediamin

m-phenylenebis(methylamine)

1-methylimidazole

1,6-Hexanediamine, 2,2,4 (or 2,4,4)-trimethyl-

· **Hazard statements**

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

(Contd. on page 11)

US



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/10/2018

Reviewed on 09/23/2015

Trade name: EL336 Hardener

(Contd. of page 10)

· **Precautionary statements**

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 05/10/2018 / 3

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3