

Printing date 06/15/2018

Reviewed on 06/15/2018

1 Identification

- **Product identifier**
- **Trade name:** P17 Black
- **Article number:** I011035-1
- **Application of the substance / the mixture** Polyester resin
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning
- **Hazard statements**
Flammable liquid and vapor.

(Contd. on page 2)

US

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: **P17 Black**

(Contd. of page 1)

Causes skin irritation.

Causes serious eye irritation.

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 2

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 2

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 25013-15-4	Vinyl toluene	10-20%
EINECS: 246-562-2		

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

PAC-1:

546-93-0	Magnesite	45 mg/m ³
7727-43-7	barium sulphate, natural	15 mg/m ³
112945-52-5	Fumed silica - untreated	18 mg/m ³
64-17-5	ethanol	1,800 ppm
1317-61-9	triiron tetraoxide	21 mg/m ³
7759-02-6	strontium sulphate	30 mg/m ³
130-15-4	1,4-naphthoquinone	0.57 mg/m ³
98-29-3	4-tert-butylcatechol	0.18 mg/m ³
8052-41-3	Stoddard solvent	300 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
108-10-1	4-methylpentan-2-one	75 ppm
142-82-5	heptane	500 ppm

PAC-2:

546-93-0	Magnesite	260 mg/m ³
----------	-----------	-----------------------

(Contd. on page 4)

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

		(Contd. of page 3)
7727-43-7	barium sulphate, natural	170 mg/m ³
112945-52-5	Fumed silica - untreated	100 mg/m ³
64-17-5	ethanol	3300* ppm
1317-61-9	triiron tetraoxide	230 mg/m ³
7759-02-6	strontium sulphate	330 mg/m ³
130-15-4	1,4-naphthoquinone	6.3 mg/m ³
98-29-3	4-tert-butylcatechol	2 mg/m ³
8052-41-3	Stoddard solvent	1,800 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
108-10-1	4-methylpentan-2-one	500 ppm
142-82-5	heptane	830 ppm

· PAC-3:

546-93-0	Magnesite	1,600 mg/m ³
7727-43-7	barium sulphate, natural	990 mg/m ³
112945-52-5	Fumed silica - untreated	630 mg/m ³
64-17-5	ethanol	15000* ppm
1317-61-9	triiron tetraoxide	1,400 mg/m ³
7759-02-6	strontium sulphate	2,000 mg/m ³
130-15-4	1,4-naphthoquinone	38 mg/m ³
98-29-3	4-tert-butylcatechol	560 mg/m ³
8052-41-3	Stoddard solvent	29500** mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
108-10-1	4-methylpentan-2-one	3000* ppm
142-82-5	heptane	5000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

(Contd. of page 4)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

25013-15-4 Vinyl toluene

PEL Long-term value: 480 mg/m³, 100 ppm

REL Long-term value: 480 mg/m³, 100 ppm

TLV Short-term value: 483 mg/m³, 100 ppm

Long-term value: 242 mg/m³, 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Breathing equipment:** Not required.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Highly viscous

Color: Black

· **Odor:** Pungent

(Contd. on page 6)

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

(Contd. of page 5)

· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	170 °C (338 °F)
· Flash point:	53 °C (127.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	1.5 hPa (1.1 mm Hg)
· Density at 20 °C (68 °F):	2.07 g/cm ³ (17.27 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	14.7 %
Water:	0.0 %
VOC content:	14.75 %
	304.7 g/l / 2.54 lb/gl
Solids content:	59.9 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 7)

US

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

 · **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

(Contd. of page 6)

11 Toxicological information

 · **Information on toxicological effects**

 · **Acute toxicity:**

 · **LD/LC50 values that are relevant for classification:**

Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	4,500 mg/kg (rabbit)
Inhalative	LC50/4 h	3,000 mg/l (mouse)

 · **Primary irritant effect:**

 · **on the skin:** Irritant to skin and mucous membranes.

 · **on the eye:** Irritating effect.

 · **Sensitization:** No sensitizing effects known.

 · **Additional toxicological information:**

 The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant

 · **Carcinogenic categories**

 · **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)	3
25013-15-4	Vinyl toluene	3
64-17-5	ethanol	1
14808-60-7	Quartz (SiO_2)	1
108-10-1	4-methylpentan-2-one	2B

 · **NTP (National Toxicology Program)**

130-15-4	1,4-naphthoquinone	R
14808-60-7	Quartz (SiO_2)	K

 · **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

 · **Toxicity**

 · **Aquatic toxicity:** No further relevant information available.

 · **Persistence and degradability** No further relevant information available.

 · **Behavior in environmental systems:**

 · **Bioaccumulative potential** No further relevant information available.

 · **Mobility in soil** No further relevant information available.

 · **Additional ecological information:**

 · **General notes:** Not known to be hazardous to water.

 · **Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

(Contd. on page 8)

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black



 · **Other adverse effects** No further relevant information available.

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|---|
| · UN-Number | |
| · DOT, IMDG, IATA | UN1866 |
| · UN proper shipping name | |
| · DOT | Resin solution |
| · IMDG, IATA | RESIN SOLUTION |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| <hr style="border-top: 1px dashed #000;"/> | |
| · IMDG, IATA | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT, IMDG, IATA | III |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · EMS Number: | F-E, <u>S-E</u> |
| · Stowage Category | A |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

(Contd. on page 9)

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

(Contd. of page 8)

· Transport/Additional information:
· DOT
· Quantity limitations

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

15 Regulatory information
· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara
· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act) (Substances not listed):

All ingredients are listed.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2) rule:

None of the ingredients is listed.

· Proposition 65
· Chemicals known to cause cancer:

 14808-60-7 Quartz (SiO₂)

108-10-1 4-methylpentan-2-one

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

108-10-1 4-methylpentan-2-one

· Carcinogenic categories
· EPA (Environmental Protection Agency)

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

108-10-1 4-methylpentan-2-one

I

142-82-5 heptane

D

· TLV (Threshold Limit Value established by ACGIH)

 14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

A4

25013-15-4 Vinyl toluene

A4

(Contd. on page 10)

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

(Contd. of page 9)

64-17-5	ethanol	A3
14808-60-7	Quartz (SiO ₂)	A2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· **Listed in CWC Regulations**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 06/15/2018 / 9

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)



BUILDING TRUST

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 06/15/2018

Reviewed on 06/15/2018

Trade name: P17 Black

(Contd. of page 10)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

US