

Printing date 01/30/2019

Reviewed on 01/30/2019

1 Identification

- **Product identifier**
- **Trade name:** SikaBiresin PX224 Part A Iso
- **Article number:** 1026131
- **Application of the substance / the mixture** Polyurethane Resin
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Supplier's Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 1)

· Hazard pictograms



GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate
Homopolymer of methylenediphenyl diisocyanate

· Hazard statements

Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves / eye protection / face protection.
[In case of inadequate ventilation] wear respiratory protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Call a poison center/doctor if you feel unwell.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2
Fire = 1
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2
Fire = 1
Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

US

(Contd. on page 3)

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 101-68-8 EINECS: 202-966-0	4,4'-methylenediphenyl diisocyanate	50-100%
CAS: 25686-28-6	Homopolymer of methylenediphenyl diisocyanate	10-20%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene	≥0.1-<0.25%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
Nitrogen oxides (NO_x)
Hydrogen cyanide (HCN)
- **Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.

(Contd. on page 4)

US

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 3)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m ³
95-63-6	1,2,4-trimethylbenzene	140 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
98-82-8	cumene	50 ppm

· PAC-2:

101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m ³
95-63-6	1,2,4-trimethylbenzene	360 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
98-82-8	cumene	300 ppm

· PAC-3:

101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
95-63-6	1,2,4-trimethylbenzene	480 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
98-82-8	cumene	730 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 5)

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 4)

· **Specific end use(s)** No further relevant information available.**8 Exposure controls/personal protection**· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:***The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.**At this time, the remaining constituent has no known exposure limits.***101-68-8 4,4'-methylenediphenyl diisocyanate**PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppmREL Long-term value: 0.05 mg/m³, 0.005 ppm
Ceiling limit value: 0.2* mg/m³, 0.02* ppm
*10-minTLV Long-term value: 0.051 mg/m³, 0.005 ppm**128-37-0 Butylated hydroxytoluene**REL Long-term value: 10 mg/m³TLV Long-term value: 2* mg/m³
*as inhalable fraction and vapor· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:***Keep away from foodstuffs, beverages and feed.**Immediately remove all soiled and contaminated clothing.**Wash hands before breaks and at the end of work.**Store protective clothing separately.**Avoid contact with the eyes and skin.*· **Breathing equipment:***In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*· **Protection of hands:**

Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.**Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.**Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*· **Material of gloves***The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

(Contd. on page 6)

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 5)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Light amber
Odor:	Characteristic
Odor threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	208 °C (406.4 °F)

- **Flash point:** 212 °C (413.6 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 520 °C (968 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

- **Vapor pressure at 20 °C (68 °F):** 0 hPa (0 mm Hg)

- **Density at 20 °C (68 °F):** 1.21 g/cm³ (10.1 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

- **Dynamic:** Not determined.

(Contd. on page 7)

US

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 6)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.2 %
VOC content:	0.20 % 2.4 g/l / 0.02 lb/gal
· Solids content:	56.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Violent reactions with -NHx, -OH and -SH- groups.
In the presence of water or humidity gas (CO₂) is produced and/or uncontrolled polymerization, possibly leading to internal pressure rises and consequent risk of container breach.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Nitrogen oxides
Carbon monoxide and carbon dioxide
(possible HCN)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2,200 mg/kg (mouse)
Dermal	LD50	>9,400 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

101-68-8 | 4,4'-methylenediphenyl diisocyanate

3

(Contd. on page 8)

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 7)

128-37-0	Butylated hydroxytoluene	3
98-82-8	cumene	2B
· NTP (National Toxicology Program)		
98-82-8	cumene	R
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 1 (Self-assessment): slightly hazardous for water
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADN, IMDG, IATA	not regulated
· UN proper shipping name	
· DOT, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA	
· Class	not regulated
· Packing group	
· DOT, IMDG, IATA	not regulated

(Contd. on page 9)

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 8)

- | | |
|--|-----------------|
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

101-68-8 | 4,4'-methylenediphenyl diisocyanate

- **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

- **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

- **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

98-82-8 | cumene

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

101-68-8 | 4,4'-methylenediphenyl diisocyanate

D, CBD

95-63-6 | 1,2,4-trimethylbenzene

II

98-82-8 | cumene

D, CBD

- **TLV (Threshold Limit Value established by ACGIH)**

128-37-0 | Butylated hydroxytoluene

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

(Contd. on page 10)

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 9)

· **Listed in CWC Regulations**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**4,4'-methylenediphenyl diisocyanate
Homopolymer of methylenediphenyl diisocyanate· **Hazard statements**Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.· **Precautionary statements**Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves / eye protection / face protection.
[In case of inadequate ventilation] wear respiratory protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 01/30/2019 / 4· **Abbreviations and acronyms:**IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)

(Contd. on page 11)



BUILDING TRUST



Safety Data Sheet
acc. to OSHA HCS

Page 11/11

Printing date 01/30/2019

Reviewed on 01/30/2019

Trade name: SikaBiresin PX224 Part A Iso

(Contd. of page 10)

VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
· *** Data compared to the previous version altered.**

US