

Printing date 07/17/2017

Reviewed on 07/17/2017

1 Identification

- **Product identifier**
- **Trade name:** EL320 Hardener
- **Article number:** R007015-1
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS07

(Contd. on page 2)

US

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: EL320 Hardener

(Contd. of page 1)

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

3,6-diazaoctanethylenediamin

- **Hazard statements**

Harmful in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 1

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 4

Fire = 1

Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 112-24-3

3,6-diazaoctanethylenediamin

50 - 100%

EINECS: 203-950-6

US

(Contd. on page 3)

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: EL320 Hardener

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

US

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: EL320 Hardener

(Contd. of page 3)

· Protective Action Criteria for Chemicals
· PAC-1:

112-24-3	3,6-diazaoctanethylenediamin	3 ppm
----------	------------------------------	-------

· PAC-2:

112-24-3	3,6-diazaoctanethylenediamin	14 ppm
----------	------------------------------	--------

· PAC-3:

112-24-3	3,6-diazaoctanethylenediamin	83 ppm
----------	------------------------------	--------

7 Handling and storage

· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters
· Components with limit values that require monitoring at the workplace:
112-24-3 3,6-diazaoctanethylenediamin

WEEL	Long-term value: 6 mg/m ³ , 1 ppm
	Skin

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: **EL320 Hardener**

(Contd. of page 4)

Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties
General Information
Appearance:

Form:	Liquid
Color:	Light yellow
Odor:	Amine-like
Odor threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/Melting range:	12 °C (54 °F)
Boiling point/Boiling range:	~278 °C (~532 °F)

Flash point: 122 °C (252 °F)

Flammability (solid, gaseous): Not applicable.

Ignition temperature: 335 °C (635 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not selfigniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined.

(Contd. on page 6)

US

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: **EL320 Hardener**

(Contd. of page 5)

Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	0.01 hPa
· Density at 20 °C (68 °F):	0.98 g/cm ³ (8.178 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.0 g/l / 0.00 lb/gl
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

112-24-3 3,6-diazaoctanethylenediamin

Oral	LD50	2500 mg/kg (rat)
Dermal	LD50	805 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

(Contd. on page 7)

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: EL320 Hardener

(Contd. of page 6)

*Corrosive**Irritant*

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** *No further relevant information available.*

- **Persistence and degradability** *No further relevant information available.*

- **Behavior in environmental systems:**

- **Bioaccumulative potential** *No further relevant information available.*

- **Mobility in soil** *No further relevant information available.*

- **Ecotoxic effects:**

- **Remark:** *Harmful to fish*

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** *Not applicable.*

- **vPvB:** *Not applicable.*

- **Other adverse effects** *No further relevant information available.*

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** *Disposal must be made according to official regulations.*

- **Recommended cleansing agent:** *Water, if necessary with cleansing agents.*

US

(Contd. on page 8)



Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: EL320 Hardener

(Contd. of page 7)

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN2259
· UN proper shipping name	
· DOT	Triethylenetetramine
· IMDG, IATA	TRIETHYLENETETRAMINE
· Transport hazard class(es)	
· DOT	
	
· Class	8 Corrosive substances
· Label	8
· IMDG, IATA	
	
· Class	8 Corrosive substances
· Label	8
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Corrosive substances
· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· Segregation Code	SG35 Stow "separated from" acids.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: **EL320 Hardener**

(Contd. of page 8)

· UN "Model Regulation": UN 2259 TRIETHYLENETETRAMINE, 8, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act) (Substances not listed):

All ingredients are listed.

· Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS05 GHS07

 · Signal word **Danger**

· Hazard-determining components of labeling:

3,6-diazaoctanethylenediamin

(Contd. on page 10)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 07/17/2017

Reviewed on 07/17/2017

Trade name: EL320 Hardener

(Contd. of page 9)

· **Hazard statements**

Harmful in contact with skin.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Do not breathe dusts or mists.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 07/17/2017 / 2

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3