

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Biresin® Kraft Kleber - Power Adhesive Part B

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

Product use : Tooling system.

#### 1.3 Details of the supplier of the safety data sheet

Company : Sika Deutschland GmbH  
Kornwestheimer Str. 103-107  
70439 Stuttgart  
Telephone : +4971180090  
E-mail address : EHS@de.sika.com

#### 1.4 Emergency telephone number

Emergency telephone number : Emergency CONTACT (24-Hour-Number):  
GBK GmbH Global Regulatory Compliance  
+49(0)6132-84463  
EHS@de.sika.com

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Type of product : Mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1B	H314: Causes severe skin burns and eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Acute aquatic toxicity, Category 1	H400: Very toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

##### Classification (67/548/EEC, 1999/45/EC)

Corrosive	R34: Causes burns.
Sensitising	R43: May cause sensitisation by skin contact.
Dangerous for the environment	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.2 Label elements

---

Country DE 000000003676

1 / 12

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Danger

Hazard statements :

H314  
H317  
H410

Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
Very toxic to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P261

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273

Avoid release to the environment.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

Hazardous components which must be listed on the label:

- 500-191-5 Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
- 223-775-9 3,6,9,12-tetra-azatetradecamethylenediamine

### 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).  
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	R43 Xi; R41-R38 N; R51/53	Skin Irrit.2; H315 Eye Dam.1; H318 Skin Sens.1; H317	>= 50 - <= 100

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

68082-29-1 500-191-5 01-2119972320-44-XXXX		Aquatic Chronic2; H411	
3,6,9,12-tetra- azatetradecamethylenediamine 4067-16-7 223-775-9 01-219485826-22-XXXX	C; R34 R43 N; R50-R53	Skin Corr.1B; H314 Skin Sens.1; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 25 - < 50

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Health injuries may be delayed.  
corrosive effects  
sensitising effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

For personal protection see section 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.
- Other data : No decomposition if stored and applied as directed.

#### 7.3 Specific end use(s)

- Specific use(s) : No data available

---

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

##### Personal protective equipment

- Eye protection : Safety glasses with side-shields  
Eye wash bottle with pure water  
Wear eye/face protection.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (0,4 mm),  
Contaminated gloves should be removed.  
Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : No special measures required.

### Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: amine-like
Odour Threshold	: No data available
Flash point	: > 101 °C
Ignition temperature	: not applicable
Lower explosion limit (Vol%)	: No data available
Upper explosion limit (Vol%)	: No data available
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

Auto-ignition temperature	:	No data available
pH	:	Note: not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Vapour pressure	:	No data available
Density	:	ca.0,98 g/cm <sup>3</sup> at 20 °C
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Viscosity, dynamic	:	ca.3.500 mPa.s at 25 °C
Viscosity, kinematic	:	> 20,5 mm <sup>2</sup> /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

### 10.4 Conditions to avoid

Conditions to avoid : No data available

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Acute toxicity

###### Components:

**3,6,9,12-tetra-azatetradecamethylenediamine :**

Acute oral toxicity : LD50 Oral rat: 1.600 mg/kg

##### Skin corrosion/irritation

###### Product

Causes severe skin burns and eye damage.

##### Serious eye damage/eye irritation

###### Product

No data available

##### Respiratory or skin sensitisation

###### Product

May cause an allergic skin reaction.

##### Germ cell mutagenicity

###### Product

Mutagenicity : No data available

##### Carcinogenicity

###### Product

Carcinogenicity : No data available

##### Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

##### Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

##### STOT - single exposure

No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

### STOT - repeated exposure

No data available

### Aspiration toxicity

No data available

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : In accordance with the EWC Waste Regulation the classification of waste is to be assigned to the jurisdiction of the origin of waste. Therefore, it is not possible to assign a particular waste identification number.  
Completely emptied packagings may be given for recycling. Empty packaging may still contain hazardous residues. Empty packaging should be removed by a licensed waste contractor. Sika has agreed disposal contracts for all packaging which is brought into circulation in Germany. For further details see [www.sika.de](http://www.sika.de)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

### SECTION 14: Transport information

#### ADR

- 14.1 UN number** : 1760  
**14.2 Description of the goods** : CORROSIVE LIQUID, N.O.S.  
(3,6,9,12-tetra-azatetradecamethylenediamine, 3,6-diazaoctanethylenediamin)  
**14.3 Class** : 8  
**14.4 Packing group** : III  
Classification Code : C9  
Labels : 8  
Tunnel restriction code : (E)  
**14.5 Environmentally hazardous** : yes

#### ADR

Transport according to chapter 3.4 (LQ) possible

#### IATA

- 14.1 UN number** : 1760  
**14.2 Description of the goods** : Corrosive liquid, n.o.s.  
(3,6,9,12-tetra-azatetradecamethylenediamine, 3,6-diazaoctanethylenediamin)  
**14.3 Class** : 8  
**14.4 Packing group** : III  
Labels : 8  
**14.5 Environmentally hazardous** : yes

#### IMDG

- 14.1 UN number** : 1760  
**14.2 Description of the goods** : CORROSIVE LIQUID, N.O.S.  
(3,6,9,12-tetra-azatetradecamethylenediamine, 3,6-diazaoctanethylenediamin)  
**14.3 Class** : 8  
**14.4 Packing group** : III  
Labels : 8  
EmS Number 1 : F-A  
EmS Number 2 : S-B  
**14.5 Marine pollutant** : yes

#### 14.6 Special precautions for user

No data available

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :



Corrosive



Dangerous for the environment

R-phrase(s)	:	R34 R43 R50/53	Causes burns. May cause sensitisation by skin contact. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S-phrase(s)	:	S26  S36/37/39  S45	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable protective clothing, gloves and eye/face protection. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Hazardous components which must be listed on the label:

- 500-191-5 Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine
- 223-775-9 3,6,9,12-tetra-azatetradecamethylenediamine

##### Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

REACH Information: All substances contained in our Products are  
- preregistered or registered by our upstream suppliers, and/or  
- preregistered or registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Water contaminating class (Germany) : WGK 2 water endangering  
Gemäß VwVws vom 30.Juli 2005

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Biresin® Kraft Kleber - Power Adhesive Part B



Revision Date 01.12.2014

Version 3.0

Print Date 09.09.2016

VOC-CH (VOCV) : no VOC duties

VOC-EU (solvent) : not applicable

### 15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

### SECTION 16: Other information

#### Full text of R-Phrases

R34	Causes burns.
R38	Irritating to skin.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R50	Very toxic to aquatic organisms.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.

#### Full text of H-Statements

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Eye Dam.	Serious eye damage
Skin Corr.	Skin corrosion
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !