

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Trade name:** M 175 RESIN (A)

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the mixture** Epoxy resin

1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

AXSON FRANCE

15 Rue de l'Equerre - F-95310 SAINT OUEN L'AUMONE

Tél. +33 (0)1 34 40 34 60

· **Further information obtainable from:** DPT HSE - +33 (0)1 34 40 34 60 - safety@axson.com

· **1.4 Emergency telephone number:** ORFILA : +33 (0)1 45 42 59 59

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS07 GHS09

· **Signal word** Warning

· **Hazard-determining components of labelling:**

reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

bisphenol-F-epichlorhydrine ; epoxy resins (molecular weight ≤ 700)

1,6-Hexanedioldiglycidyl ether

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P273 Avoid release to the environment.

P305+P351+P338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2017

Version number 5

Revision: 09.05.2016

Trade name: M 175 RESIN (A)

(Contd. of page 1)

- **Additional information:**
EUH205 Contains epoxy constituents. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5 Reg.nr.: 01-2119456619-26	reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 28064-14-4 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	bisphenol-F-epichlorhydrine ; epoxy resins (molecular weight ≤ 700) Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 16096-31-4 EINECS: 240-260-4 Reg.nr.: 01-2119463471-41	1,6-Hexanedioldiglycidyl ether Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5-10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:
Hydrogen chloride (HCl)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear fully protective suit.
Wear self-contained respiratory protective device.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 3)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2017

Version number 5

Revision: 09.05.2016

Trade name: M 175 RESIN (A)

(Contd. of page 2)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Protection of hands:**



Protective gloves

- **Material of gloves**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
Synthetic rubber gloves

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2017

Version number 5

Revision: 09.05.2016

Trade name: M 175 RESIN (A)

(Contd. of page 3)

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

Tightly sealed goggles

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Pasty
Colour:	Light grey
Odour:	Weak, characteristic

- **Change in condition**

Melting point/Melting range: NA °C

Boiling point/Boiling range: >200 °C (DIN 53171)

- **Flash point:** >110 °C (ISO 2719)

- **Ignition temperature:** >300 °C (DIN 51 794)

- **Decomposition temperature:** >200 °C (DIN 53171)

- **Self-igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Density at 25 °C:** 0.6 g/cm³ (ISO 1675:1985)

- **Solubility in / Miscibility with water:**

Insoluble.

- **organic solvents:** Soluble in many organic solvents.

- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

- **10.2 Chemical stability**

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions**

May produce violent reactions with bases and numerous organic substances including alcohols and amines. Exothermic polymerisation.

- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2017

Version number 5

Revision: 09.05.2016

Trade name: M 175 RESIN (A)

(Contd. of page 4)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Irritant gases/vapours

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral	LD50	11400 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

28064-14-4 bisphenol-F-epichlorhydrine ; epoxy resins (molecular weight ≤ 700)

Oral	LD50	> 2000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>2000 mg/kg (rabbit)
--------	------	----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

25068-38-6 reaction product: bisphenol A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

LC50 (96h)	1.3 mg / l (fish)
------------	-------------------

LC50 (48h)	2.1 mg/l (daphnia)
------------	--------------------

LC50 (72h)	>11 mg/l (alga)
------------	-----------------

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
At present there are no ecotoxicological assessments.
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2017

Version number 5

Revision: 09.05.2016

Trade name: M 175 RESIN (A)

(Contd. of page 5)

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of the product by burning in a suitable incinerator or bury in an approved landfill following all applicable local and/or national regulations.

· **European waste catalogue**

20 01 27	paint, inks, adhesives and resins containing dangerous substances
----------	---

· **Uncleaned packaging:**

· **Recommendation:**

Empty containers may not be disposed of unless any remaining material adhering to the internal walls has been removed.

Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN3077

· **14.2 UN proper shipping name**

· **ADR**

3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (epoxy resins)

· **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (epoxy resins), MARINE POLLUTANT

· **IATA**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (epoxy resins)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class**

9 Miscellaneous dangerous substances and articles.

· **Label**

9

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

· **Marine pollutant:**

Yes

Symbol (fish and tree)

· **Special marking (ADR):**

Symbol (fish and tree)

· **Special marking (IATA):**

Symbol (fish and tree)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2017

Version number 5

Revision: 09.05.2016

Trade name: M 175 RESIN (A)

(Contd. of page 6)

- | | |
|--|---|
| · 14.6 Special precautions for user | Warning: <i>Miscellaneous dangerous substances and articles.</i> |
| · Danger code (Kemler): | 90 |
| · EMS Number: | F-A,S-F |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| ----- | |
| · ADR | |
| · Limited quantities (LQ) | 5 kg |
| · Transport category | 3 |
| · Tunnel restriction code | E |
| · UN "Model Regulation": | UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (epoxy resins), 9, III |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2017

Version number 5

Revision: 09.05.2016

Trade name: M 175 RESIN (A)

(Contd. of page 7)

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB