



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/12/2018

1 Identification

- **Product identifier**
- **Trade name:** APG 1750 S Neutral
- **Article number:** 1025928
- **Application of the substance / the mixture** Sprayable polyester gel coat
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 1)

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word *Danger*

· Hazard-determining components of labeling:

Vinyl toluene
methyl methacrylate
Naphtha (petroleum), hydrotreated heavy
Stoddard solvent

· Hazard statements

Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause respiratory irritation.
May be fatal if swallowed and enters airways.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2
Fire = 2
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



HEALTH 2 Health = 2
FIRE 2 Fire = 2
REACTIVITY 0 Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 3)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 25013-15-4 EINECS: 246-562-2	Vinyl toluene	20-50%
CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate	1-5%
CAS: 136-52-7 EINECS: 205-250-6	cobalt(II) 2-ethylhexanoate	0.1-1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 3)

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

80-62-6	methyl methacrylate	17 ppm
112945-52-5	Fumed silica - untreated	18 mg/m ³
64-17-5	ethanol	1,800 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
123-31-9	1,4-dihydroxybenzene	3 mg/m ³
150-76-5	mequinol	15 mg/m ³
108-10-1	4-methylpentan-2-one	75 ppm
130-15-4	1,4-naphthoquinone	0.57 mg/m ³
8052-41-3	Stoddard solvent	300 mg/m ³
98-29-3	4-tert-butylcatechol	0.18 mg/m ³
142-82-5	heptane	500 ppm

· **PAC-2:**

80-62-6	methyl methacrylate	120 ppm
112945-52-5	Fumed silica - untreated	100 mg/m ³
64-17-5	ethanol	3300* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m ³
14808-60-7	Quartz (SiO ₂)	33 mg/m ³
123-31-9	1,4-dihydroxybenzene	20 mg/m ³
150-76-5	mequinol	49 mg/m ³
108-10-1	4-methylpentan-2-one	500 ppm
130-15-4	1,4-naphthoquinone	6.3 mg/m ³
8052-41-3	Stoddard solvent	1,800 mg/m ³
98-29-3	4-tert-butylcatechol	2 mg/m ³
142-82-5	heptane	830 ppm

· **PAC-3:**

80-62-6	methyl methacrylate	570 ppm
112945-52-5	Fumed silica - untreated	630 mg/m ³
64-17-5	ethanol	15000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m ³
14808-60-7	Quartz (SiO ₂)	200 mg/m ³
123-31-9	1,4-dihydroxybenzene	120 mg/m ³

(Contd. on page 5)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 4)

150-76-5	mequinol	320 mg/m ³
108-10-1	4-methylpentan-2-one	3000* ppm
130-15-4	1,4-naphthoquinone	38 mg/m ³
8052-41-3	Stoddard solvent	29500** mg/m ³
98-29-3	4-tert-butylcatechol	560 mg/m ³
142-82-5	heptane	5000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

25013-15-4 Vinyl toluene

PEL	Long-term value: 480 mg/m ³ , 100 ppm
REL	Long-term value: 480 mg/m ³ , 100 ppm
TLV	Short-term value: 483 mg/m ³ , 100 ppm Long-term value: 242 mg/m ³ , 50 ppm

80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m ³ , 100 ppm
REL	Long-term value: 410 mg/m ³ , 100 ppm
TLV	Short-term value: 410 mg/m ³ , 100 ppm Long-term value: 205 mg/m ³ , 50 ppm
DSEN	

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 6)

US

Trade name: APG 1750 S Neutral

(Contd. of page 5)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Thixotropic Paste

Color: Neutral

- **Odor:** Aromatic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 36 °C (96.8 °F)

- **Flash point:** 53 °C (127.4 °F)

(Contd. on page 7)

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 6)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	494 °C (921.2 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	5.2 Vol %
· Vapor pressure at 20 °C (68 °F):	1 hPa (0.8 mm Hg)
· Density at 20 °C (68 °F):	1.29 g/cm ³ (10.77 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	28.6 %
VOC content:	32.78 %
	422.9 g/l / 3.53 lb/gl
Solids content:	30.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
- ?
- Carbon monoxide and carbon dioxide

US

(Contd. on page 8)

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 7)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

25013-15-4	Vinyl toluene	3
80-62-6	methyl methacrylate	3
64-17-5	ethanol	1
136-52-7	cobalt(II) 2-ethylhexanoate	2B
14808-60-7	Quartz (SiO ₂)	1
123-31-9	1,4-dihydroxybenzene	3
108-10-1	4-methylpentan-2-one	2B

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
130-15-4	1,4-naphthoquinone	R

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

US

(Contd. on page 9)






Trade name: APG 1750 S Neutral

(Contd. of page 8)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, IMDG, IATA	UN1866
· UN proper shipping name	
· DOT	Resin solution
· IMDG	RESIN SOLUTION (1,4-dihydroxybenzene), MARINE POLLUTANT
· IATA	RESIN SOLUTION
· Transport hazard class(es)	
· DOT	
	 
· Class	3 Flammable liquids
· Label	3
· IMDG	
	 
· Class	3 Flammable liquids
· Label	3
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	III

(Contd. on page 10)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 9)

· Environmental hazards:	Product contains environmentally hazardous substances: 1,4-dihydroxybenzene
· Marine pollutant:	Yes Yes Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· Remarks:	Special marking with the symbol (fish and tree).
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

123-31-9	1,4-dihydroxybenzene
----------	----------------------

· **Section 313 (Specific toxic chemical listings):**

80-62-6	methyl methacrylate
---------	---------------------

136-52-7	cobalt(II) 2-ethylhexanoate
----------	-----------------------------

· **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

1317-65-3	Calcium Carbonate
-----------	-------------------

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

(Contd. on page 11)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 10)

108-10-1	4-methylpentan-2-one
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
64-17-5	ethanol
108-10-1	4-methylpentan-2-one

· **Carcinogenic categories**

· EPA (Environmental Protection Agency)		
80-62-6	methyl methacrylate	E, NL
108-10-1	4-methylpentan-2-one	I
142-82-5	heptane	D

· **TLV (Threshold Limit Value established by ACGIH)**

25013-15-4	Vinyl toluene	A4
80-62-6	methyl methacrylate	A4
64-17-5	ethanol	A3
14808-60-7	Quartz (SiO ₂)	A2
123-31-9	1,4-dihydroxybenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· **Listed in CWC Regulations**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

Vinyl toluene
 methyl methacrylate
 Naphtha (petroleum), hydrotreated heavy
 Stoddard solvent

· **Hazard statements**

Flammable liquid and vapor.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 Suspected of causing cancer.
 May cause respiratory irritation.

(Contd. on page 12)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/29/2018

Reviewed on 04/12/2018

Trade name: APG 1750 S Neutral

(Contd. of page 11)

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 05/29/2018 / 9

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1