



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

### 1 Identification

- **Product identifier**
- **Trade name:** ProSeal EZ15 Hardener
- **Article number:** 1852089
- **Application of the substance / the mixture** Epoxy curing agent
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**  
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:  
31200 Stephenson Hwy  
Madison Heights, MI 48071  
USA

Manufacturing Site:  
1611 Hults Drive  
Eaton Rapids, MI 48827  
USA  
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (248) 588-2270  
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS06 Skull and crossbones

Acute Tox. 2      H330 Fatal if inhaled.



GHS08 Health hazard

Repr. 2      H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1B      H314 Causes severe skin burns and eye damage.

Eye Dam. 1      H318 Causes serious eye damage.



GHS07

Acute Tox. 4      H302 Harmful if swallowed.

Acute Tox. 4      H312 Harmful in contact with skin.

(Contd. on page 2)

US

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 1)

*Skin Sens. 1 H317 May cause an allergic skin reaction.*

*Aquatic Acute 3 H402 Harmful to aquatic life.*

*Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.*

· **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*2,2'-iminodiethylamine*

*2-piperazin-1-ylethylamine*

*bisphenol A*

*m-phenylenebis(methylamine)*

*trimethylhexane-1,6-diamine*

· **Hazard statements**

*Harmful if swallowed or in contact with skin.*

*Fatal if inhaled.*

*Causes severe skin burns and eye damage.*

*May cause an allergic skin reaction.*

*Suspected of damaging fertility or the unborn child.*

*Harmful to aquatic life.*

*Harmful to aquatic life with long lasting effects.*

· **Precautionary statements**

*Avoid breathing dust/fume/gas/mist/vapors/spray*

*Do not breathe dusts or mists.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*[In case of inadequate ventilation] wear respiratory protection.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Immediately call a poison center/doctor.*

*Specific treatment is urgent (see on this label).*

*Take off contaminated clothing and wash it before reuse.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



*Health = 3*

*Fire = 1*

*Reactivity = 0*

(Contd. on page 3)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = *3
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 111-40-0 EINECS: 203-865-4	2,2'-iminodiethylamine	20-50%
CAS: 80-05-7 EINECS: 201-245-8	bisphenol A	10-20%
CAS: 140-31-8 EINECS: 205-411-0	2-piperazin-1-ylethylamine	10-20%
CAS: 98-54-4 EINECS: 202-679-0	4-tert-butylphenol	10-20%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine)	≥5-<10%
CAS: 25620-58-0 EINECS: 247-134-8	trimethylhexane-1,6-diamine	≥5-<10%
CAS: 84852-15-3 EINECS: 284-325-5	4-nonylphenol, branched	≥1-<2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
Remove breathing apparatus only after contaminated clothing have been completely removed.  
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Immediately call a doctor.  
Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 4)

US



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Wear self-contained respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

111-40-0	2,2'-iminodiethylamine	3 ppm
80-05-7	bisphenol A	15 mg/m <sup>3</sup>
140-31-8	2-piperazin-1-ylethylamine	6.4 mg/m <sup>3</sup>
98-54-4	4-tert-butylphenol	1.5 mg/m <sup>3</sup>
84852-15-3	4-nonylphenol, branched	3.9 mg/m <sup>3</sup>

· **PAC-2:**

111-40-0	2,2'-iminodiethylamine	8.5 ppm
80-05-7	bisphenol A	110 mg/m <sup>3</sup>
140-31-8	2-piperazin-1-ylethylamine	71 mg/m <sup>3</sup>
98-54-4	4-tert-butylphenol	40 mg/m <sup>3</sup>

(Contd. on page 5)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 4)

84852-15-3	4-nonylphenol, branched	43 mg/m <sup>3</sup>
<b>· PAC-3:</b>		
111-40-0	2,2'-iminodiethylamine	51 ppm
80-05-7	bisphenol A	650 mg/m <sup>3</sup>
140-31-8	2-piperazin-1-ylethylamine	420 mg/m <sup>3</sup>
98-54-4	4-tert-butylphenol	240 mg/m <sup>3</sup>
84852-15-3	4-nonylphenol, branched	260 mg/m <sup>3</sup>

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

#### 111-40-0 2,2'-iminodiethylamine

REL	Long-term value: 4 mg/m <sup>3</sup> , 1 ppm Skin
TLV	Long-term value: 4.2 mg/m <sup>3</sup> , 1 ppm Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

(Contd. on page 6)

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 5)

- **Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

- **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

- **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

- **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

- **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Amber colored
<b>Odor:</b>	Amine-like
<b>Odor threshold:</b>	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	>200 °C (>392 °F)

- **Flash point:** 94 °C (201.2 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 315 °C (599 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

(Contd. on page 7)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

Trade name: ProSeal EZ15 Hardener

(Contd. of page 6)

· <b>Explosion limits:</b>	
<b>Lower:</b>	1 Vol %
<b>Upper:</b>	10.5 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	0.5 hPa (0.4 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	1.01 g/cm <sup>3</sup> (8.43 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>VOC content:</b>	0.00 % 0.0 g/l / 0.00 lb/gl
<b>Solids content:</b>	27.5 %
· <b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**  
?  
Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

#### · LD/LC50 values that are relevant for classification:

Dermal	LD50	1,090 mg/kg (rabbit)
Inhalative	LC50/4 h	0.3 mg/l (rat)

#### 111-40-0 2,2'-iminodiethylamine

Oral	LD50	1,553 mg/kg (rat)
Dermal	LD50	1,045 mg/kg (rabbit)

(Contd. on page 8)

US



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 7)

Inhalative	LC50/4 h	0.3 mg/l (rat)
<b>80-05-7 bisphenol A</b>		
Oral	LD50	3,250 mg/kg (rat)
Dermal	LD50	3,000 mg/kg (rabbit)
<b>140-31-8 2-piperazin-1-ylethylamine</b>		
Oral	LD50	2,110 mg/kg (rat)
Dermal	LD50	866 mg/kg (rabbit)
<b>98-54-4 4-tert-butylphenol</b>		
Oral	LD50	2,951 mg/kg (rat)
Dermal	LD50	2,288 mg/kg (rabbit)
<b>1477-55-0 m-phenylenebis(methylamine)</b>		
Oral	LD50	1,040 mg/kg (rat)
Inhalative	LC50/4 h	2.4 mg/l (rat)
<b>25620-58-0 trimethylhexane-1,6-diamine</b>		
Oral	LD50	900 mg/kg (rat)

· **Primary irritant effect:**

· **on the skin:** Caustic effect on skin and mucous membranes.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Corrosive

Irritant

Very toxic

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

96 hr LC50 0.128 mg/l (Fathead minnow)

(Contd. on page 9)

US





BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

Trade name: ProSeal EZ15 Hardener

(Contd. of page 8)

### 140-31-8 2-piperazin-1-ylethylamine

48 hr EC50	58 mg/l (Invertabrates)
96 hr LC50	2,190 mg/l (Fish)
72 or 96 hr ErC50	1,000 mg/l (Algea)

### 98-54-4 4-tert-butylphenol

48 hr EC50	3.4 mg/l (daphnia)
96 hr LC50	4.71 mg/l (Fathead minnow)

### 1477-55-0 m-phenylenebis(methylamine)

72 or 96 hr ErC50	12 mg/l (Chaetogammarus marinus)
-------------------	----------------------------------

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 2 (Self-assessment): hazardous for water*  
*Do not allow product to reach ground water, water course or sewage system.*  
*Must not reach bodies of water or drainage ditch undiluted or unneutralized.*  
*Danger to drinking water if even small quantities leak into the ground.*  
*Harmful to aquatic organisms*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
*Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |                                  |   |
|----------------------------------|---|
| · <b>UN-Number</b>               |   |
| · <b>DOT</b>                     | NA2735  |
| · <b>IMDG, IATA</b>              | UN2735  |
| · <b>UN proper shipping name</b> |   |
| · <b>DOT</b>                     | Amines, liquid, corrosive, n.o.s. (Diethylenetriamine, m-phenylenebis(methylamine)) |

(Contd. on page 10)

US

Printing date 05/31/2018

Reviewed on 05/18/2015

Trade name: ProSeal EZ15 Hardener

(Contd. of page 9)

· **IMDG, IATA** *AMINES, LIQUID, CORROSIVE, N.O.S.*  
*(DIETHYLENETRIAMINE, m-phenylenebis(methylamine))*

· **Transport hazard class(es)**· **DOT**

· **Class** *8 Corrosive substances*  
 · **Label** *8*

· **IMDG, IATA**

· **Class** *8 Corrosive substances*  
 · **Label** *8*

· **Packing group**· **DOT, IMDG, IATA** *II*· **Environmental hazards:**· **Marine pollutant:** *No*· **Special precautions for user** *Warning: Corrosive substances*· **Danger code (Kemler):** *80*· **EMS Number:** *F-A,S-B*· **Segregation groups** *Alkalis*· **Stowage Category** *A*· **Segregation Code** *SG35 Stow "separated from" acids.*· **Transport in bulk according to Annex II of****MARPOL 73/78 and the IBC Code** *Not applicable.*· **Transport/Additional information:**· **DOT**

· **Quantity limitations** *On passenger aircraft/rail: 1 L*  
*On cargo aircraft only: 30 L*

· **IMDG**· **Limited quantities (LQ)** *1L*

· **Excepted quantities (EQ)** *Code: E2*  
*Maximum net quantity per inner packaging: 30 ml*  
*Maximum net quantity per outer packaging: 500 ml*

· **UN "Model Regulation":**

*UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.*  
*(DIETHYLENETRIAMINE, M-PHENYLENEBIS(METHYLAMINE)),*  
*8, II*

US

(Contd. on page 11)

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 10)

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

80-05-7 bisphenol A

84852-15-3 4-nonylphenol, branched

- **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

- **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

- **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

80-05-7 bisphenol A

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Listed in CWC Regulations**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05

GHS06

GHS07

GHS08

- **Signal word** Danger

(Contd. on page 12)



BUILDING TRUST



## Safety Data Sheet

acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 11)

· **Hazard-determining components of labeling:**

2,2'-iminodiethylamine  
2-piperazin-1-ylethylamine  
bisphenol A  
m-phenylenebis(methylamine)  
trimethylhexane-1,6-diamine

· **Hazard statements**

Harmful if swallowed or in contact with skin.  
Fatal if inhaled.  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
Suspected of damaging fertility or the unborn child.  
Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

Do not breathe dusts or mists.  
Wear protective gloves/protective clothing/eye protection/face protection.  
[In case of inadequate ventilation] wear respiratory protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
Immediately call a poison center/doctor.  
Specific treatment is urgent (see on this label).  
Take off contaminated clothing and wash it before reuse.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 05/31/2018 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit

(Contd. on page 13)



BUILDING TRUST



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 05/31/2018

Reviewed on 05/18/2015

**Trade name: ProSeal EZ15 Hardener**

(Contd. of page 12)

*REL: Recommended Exposure Limit*

*Acute Tox. 4: Acute toxicity – Category 4*

*Acute Tox. 2: Acute toxicity – Category 2*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Repr. 2: Reproductive toxicity – Category 2*

*Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

US