



EPOXY INFUSION SYSTEMS

ROOM & HIGH TEMPERATURE

HIGH PERFORMANCE ▪ BROAD RANGE OF APPLICATIONS






BUILDING TRUST



EPOXY INFUSION SYSTEMS – ROOM TEMPERATURE

Product	Brand	Tg (°F)	Mix Ratio	Cured Color	Mixed Viscosity (cps)	Pot Life (min/g)	Description & Applications
EL-360* (* special order only)		170	100				Intermediate-temperature range system with excellent mechanical properties for fabrication of performance composite parts and structures
EL-360 H			27	lgt amber	326	44/200	
EL-360-1 H			30	lgt amber	326	70/200	
EL-360-2 H			32	lgt amber	280	560/100	
Marine 820		180	100				UV-resistant, general purpose, low viscosity system used for fabrication of laminated or infusion molded composite parts and structures
Marine 822 H			18	lgt amber	650	30/200	
Marine 823 H			18	lgt amber	350	45/200	
Marine 824 H			18	lgt amber	425	60/200	
ProInfusion RT			100				High clarity epoxy infusion/laminating system for production of composite structures and marine applications
Fast H		183	27	clear	300	25/150	
Medium H		185	27	clear	300	90/150	
Slow H		192	27	clear	300	160/150	
Epolam 2015		190	100				Marine system for production of composite structures and tooling by hand layup, RTM, and infusion methods
Epolam 2015 H			32	clear	550	140/500	

EPOXY INFUSION SYSTEMS – HIGH TEMPERATURE

ProInfusion HT		287	100				High clarity epoxy infusion/laminating system for production of composite structures and marine applications
High Temp H			27	clear	550	275/150	
Epolam 2090		401	100				Ultra-high temperature system for production of composite tooling and structures by vacuum bagging and infusion processes
Epolam 2026 H			53	amber	650	1,500/150	
Epolam 2092		437	100				Ultra-high temperature, heat curing epoxy infusion system for composite molds and structures
Epolam 2092 H			50	amber	550	400/500	

SikaAxson US

31200 Stephenson Hwy.
Madison Heights, MI 48071
Phone: +1 (248) 588-2270
Toll Free: +1 (800) 344-7776
Fax: +1 (248) 588-5909
Email: axsonmh@axson.com
www.sikaaxson.us

SikaAxson US proudly manufactures the following brands:



The information in this document reflects representative values at the time of publication. Please consult Technical Data Sheets (TDS) for additional information. Visit our website to view other products and technical / safety data. SikaAxson US Terms and Conditions apply to all sales.